



INDIA'S No.1 BIKE IN 125cc[^]

GLAMOUR

— STAND OUT, STAY AHEAD —





SPECIFICATIONS




ENGINE	
Type	Air cooled, 4 - stroke single cylinder OHC
Displacement	124.7 cc
Maximum Power	6.72 kW (9.1 Ps) @7000 rpm
Maximum Torque	10.35 N-m @4000 rpm
Bore x Stroke	52.4 x 57.8 mm
Compression Ratio	9.1:1
Starting	Self Start / Kick Start
Ignition	AMI - Advanced Microprocessor Ignition System
TRANSMISSION	
Clutch	Multiplate wet
Gear box	4 - speed constant mesh
Chassis Type	Tubular Double Cradle Type
SUSPENSION	
Front	Telescopic Hydraulic Shock Absorbers
Rear	Swing Arm with Hydraulic Shock Absorbers
BRAKES	
Front	Disc
	Drum
Rear	Drum
	Drum
	240 mm Dia; Pad - Non Asbestos type
	Internal expanding shoe type - 130 mm
	Liners - Non Asbestos type
	Internal expanding shoe type - 130 mm
	Liners - Non Asbestos type
TYRES	
Tyre Size	Front 2.75 x 18 - 42 P / 4 PR
	Rear 3.00 x 18 - 52 P / 6 PR

ELECTRICALS	
Battery	12 V - 3 Ah MF Battery
Head Lamp	12 V - 35 W / 35 W - Halogen Bulb (Multi-Reflector Type)
Tail / Stop Lamp	12 V - 5 / 21 W (Multi-Reflector)
Turn Signal Lamp	12 V - 10 W (Amber Bulb) x 4 nos (MFR - Clear Lens)
Engine Oil Grade	SAE 10 W 30 SJ Grade
Fuel Tank Capacity	13.6 litre (Min)
Reserve	1 litre (Usable Reserve)
DIMENSIONS	
LxWxH	2005 mm X 735 mm X 1070 mm
Wheelbase	1265 mm
Ground clearance	150 mm
WEIGHT	
Kerb weight	125 Kg (Kick) / 129 Kg (Self)



FEATURES



Regd. Office: Hero MotoCorp Ltd., 34, Community Centre, Basant Lok, Vasant Vihar, New Delhi - 110057, India. CIN: L35911DL1984PLC017354. Accessories and features shown may not be part of standard fitment. Always wear a helmet while riding a two wheeler. For further information, visit www.heromotocorp.com. *As per SIAM's dispatch numbers for the period April - November 2016.

GLAMOUR

